```
print $quoteBot1->getQuote();
print $quoteBot2->getQuote();
```

```
Output:
Forget it, Donny You're out of your element.
Don't get uptight with me, man.
```

We've made two `QuoteBot` objects, but with the second one we've swapped out the array of quotes (which we can do because the access level to `quoteStash` is `public`), and now our two bots have diverged. One is clearly quoting a different film to the other. When the two objects were created they had identical state: methods and properties were the same. By changing the internal state of `$quoteBot2` we change its output. If we were to introduce a third instance of `QuoteBot` into our code, it would behave like `$quoteBot1` because it would have the initial state as per the class definition.

Let's say we want to restrict access to `quoteStash`, because we never intended the quotes to be changed. To hide that array data from code outside the class, we use the keyword `private`:

```
$quoteBot2 = new QuoteBot();

$quoteBot2->quoteStash = [
    "Don't get uptight with me, man." . PHP_EOL,
    "I could take double anything you could." . PHP_EOL,
    "Very, very foolish words, man." . PHP_EOL,
];

class QuoteBot
{
    private array $quoteStash = [
        "Obviously, you're not a golfer." . PHP_EOL,
        "That's just, like, your opinion, man." . PHP_EOL,
        "Forget it, Donny You're out of your element." . PHP_EOL,
    ];

    // we'll need some more code in a moment...
}
```