```
Output:
Let's spit on our hands and get to work.
Welcome to Los Angeles, Mr. Fink.
I tried to show you... something beautiful.
That's all, folks.
```

The order of events is as follows. `$bot = new FinkBot()` instantiates the object, which triggers the call to `__construct()` gives us our first line of output. `unset($bot)` (after the `print` statement) removes the only reference to the object, which triggers the `__destruct()` method immediately and generates the third line of output. There's a final `print` statement just to demonstrate that PHP is still running at this point. Had we not called `unset()`, the destructor method of `$bot` would be invoked after the final statement of our program. Bear in mind that destructors that are triggered by PHP shutdown can be called in any order.

Magic Methods

PHP classes can define specially named methods which will be called when certain operations are performed on objects of the class, these are known as *magic methods*. We've already seen two magic methods: `__construct()` and `__destruct()` and learned that they are always called when objects are created and destroyed. There are several other magic methods which can be implemented, which will then be called on an object during certain operations. For example, if an object is referenced in a string context PHP will check for a `__toString()` method (an emit an error if none is available):

```
class Finkbot
{
    public function __toString(): string
    {
        return "I tried to show you... something beautiful." . PHP_EOL;
    }
}

$finkBot = new Finkbot();

print "What does Finkbot say? {$finkBot}";

Output:
What does Finkbot say? I tried to show you... something beautiful.
```