If you are following a coding standard such as PSR-1, classes must be declared in a namespace of at least one level and, in addition, must follow the autoloading standard of PSR-4. This means that namespace hierarchy (top-level namespace, sub-namespace, sub-sub-namespace, etc.) can be mapped to the filesystem storing the source code. A typical PSR-4 compliant project might have an "entry" script named `main.php` and store its classes in a directory structure that maps to the namespace structure of the project:

```
$ ls -la
drwxrwxrwt  16 user   wheel  512 21 Aug 20:42 .
drwxr-xr-x   6 user   wheel  192  1 Aug  1970 ..
drwxr-xr-x   4 user   wheel  128 21 Aug 20:42 Application
-rwxr-xr-x   1 user   wheel   46  6 Aug 12:46 main.php

$ ls -la Application
drwxr-xr-x   4 user   wheel  128 21 Aug 20:42 .
drwxrwxrwt  16 user   wheel  512 21 Aug 20:42 ..
drwxr-xr-x   2 user   wheel   64 21 Aug 20:42 Email

$ ls -la Application/Email
drwxr-xr-x   3 user   wheel   96 21 Aug 20:46 .
drwxr-xr-x   4 user   wheel  128 21 Aug 20:42 ..
-rw-r--r--   1 user   wheel    0 21 Aug 20:46 Manager.php
```

The first few lines of `Application/Email/Manager.php` will therefore look like this:

```
<?php

namespace Application\Email;

class Manager
{
    // rest of declaration
```

By setting up namespaced classes in this way, it is possible for PHP to locate and load classes on demand using a mechanism called autoloading, which just so happens to be the very next section of this chapter…