Given the following filesystem layout (using the linux `tree` command, macOS users might need to run `$ brew install tree` first):

```
$ tree --charset=ascii
.
|-- 10.05_main.php
`-- MyApplication
    |-- SomeClass.php
    `-- SubNamespace
        |-- SomeOtherClass.php
        `-- ThisClassOverHere.php
```

... then inside `10.05_main.php` we can register an autoload function like this:

```
spl_autoload_register(function ($class) {
    print "LOADING : {$class} from namespace " . __NAMESPACE__ . PHP_EOL;
    $class = str_replace("\\", DIRECTORY_SEPARATOR, $class);
    require __DIR__ . DIRECTORY_SEPARATOR . $class . '.php';
});
```

The magic constant `__NAMESPACE__` will evaluate to the current namespace (more on this very shortly). Our namespaced classes look like this:

```
// MyApplication/SomeClass.php
namespace MyApplication;

use MyApplication\SubNamespace\SomeOtherClass;
use MyApplication\SubNamespace\ThisClassOverHere;

class SomeClass
{
    private $otherClass;
    private $thisClassOverHere;

    public function __construct()
    {
        $this->otherClass = new SomeOtherClass();
        $this->thisClassOverHere = new ThisClassOverHere()
    }
}
```