to make use of it. When your script calls a locale-aware function (e.g., for collation or number formatting), the underlying C code will hook into the system library and follow the rules defined there.

strcoll()

The `strcoll()` function, which works in a similar way to `strcmp()`, is able to interpret bytes via the system's locale setting. The `default_locale` can be set in PHP config (and we've covered PHP configuration in an earlier chapter), but here we're going to use `setlocale()`, which gets and sets the desired system locale at runtime. Here's a quick example: we have four lovely Turkish friends – Şimal, Çağari, Alek, and Maya – and we're going to put them in name order. We'll use the `usort()` function (details available in Chapter 5, "Array") in combination with `strcmp()` and `strcoll()` as the comparison callback functions.

```
$turkishFriends = ["\u{15e}imal", "\u{c7}a\u{11f}ari", "Alek", "Maya",];
usort($turkishFriends, 'strcmp');
print_r($turkishFriends);

setlocale(LC_COLLATE, 'tr_TR.UTF-8');
usort($turkishFriends, 'strcoll');
print_r($turkishFriends);

Output:
Array
(
    [0] => Alek
    [1] => Maya
    [2] => Çağari
    [3] => Şimal
)
Array
(
    [0] => Alek
    [1] => Çağari
    [2] => Maya
    [3] => Şimal
)
```