```
$chars = mb_str_split("\u{5408}\u{6c23}\u{9053}"); // 合氣道 - will be
                                                   UTF-8 encoded on
                                                   *nix systems
foreach ($chars as $char) {
    print $char . PHP_EOL;
}
```

```
Output:
合
氣
道
```

Like `str_split()`, `mb_str_split()` also accepts an integer argument to control the character width of the returned array elements; it also accepts a third string argument to specify the encoding used in the input data.

```
$utf16str = "\x54\x08\x62\xc3\x90\x53"; // 合氣道 - raw byte values for
                                        UTF-16 encoding
$chars = mb_str_split($utf16str, 1, 'UTF-16');
foreach ($chars as $char) {
    print bin2hex($char) . PHP_EOL;
}
```

```
Output:
5408
62c3
9053
```

str_getcsv()

`str_getcsv()` is very similar to `explode()`: it takes a single string as input and returns an array of strings, and the input string is parsed according to the CSV (comma-separated values) format. Note the `escape:` named parameter on both `str_getcsv()` calls: This parameter (either named or positional form) is required from PHP 8.4 onwards (and will emit an `E_DEPRECATED` error if omitted):

```
$species = "Dentrassis,Dolphins,G'Gugvuntt,Vl'hurgs,Golgafrinchans";
print_r(str_getcsv($species, escape: '\\'));
```

```
$species = "Dentrassis|Dolphins|G'Gugvuntt|Vl'hurgs|Golgafrinchans";
```