have matching `networks` and `volumes` nodes: both services will therefore be using the `internal` shared network so they can send network packets to each other, and both services will also mount the host path of `./` (the current directory) on the container path `/var/www/html`. In addition, `services.nginx` has a `ports` node which instructs `dockerd` to listen to TCP 8080 on the host and forward all traffic to the container on TCP 80 (we'll configure `nginx` to listen to that port in a moment).

`services.nginx` also has a `build` node. We need this because we're going to make a small but very important change to the `nginx:1.25` base image, we'll actually be building a new image (which is quite exciting if you're anything like me!) and running our `nginx` container from that. Notice that `services.nginx.build.dockerfile` has the value `./Dockerfile`, this tells `dockerd` to read `./Dockerfile` for the build instructions, let's create that next.

```
FROM nginx:1.25
ADD default.conf /etc/nginx/conf.d
```

This is very simple, it simply tells `dockerd` that our image is built on top of `nginx:1.25` and we'd like to put a file into the container's filesystem path of `/etc/nginx/conf.d` (we're overwriting the default container configuration with our own) and yes, you've guessed it, we now need to create the `default.conf` file…

```
server {
    listen 0.0.0.0:80;
    root /var/www/html;
    location / {
        index index.php index.html;
    }
    location ~ \.php$ {
        include fastcgi_params;
        fastcgi_pass php-fpm:9000;
        fastcgi_index index.php;
        fastcgi_param SCRIPT_FILENAME $document_root/$fastcgi_script_name;
    }
}
```