To convert case between upper and lower, you can use `strtolower()` and its counterpart `strtoupper()`. These two functions only work on the ASCII range characters *0x41* to *0x5a*, like so:

```
print strtolower("IT DOES WHAT IT SAYS ON THE TIN.") . PHP_EOL;
print strtoupper("AnD nOt mUcH eLsE.") . PHP_EOL;
```

```
Output:
it does what it says on the tin.
AND NOT MUCH ELSE.
```

These two functions work with UTF-8 in that they will convert the case of ASCII range bytes in a UTF-8 string (as we've seen, UTF-8 cleverly avoids multi-byte characters being mistaken for ASCII), but that is all these two functions do: adding (or subtracting) decimal *32* for each byte value in the a–z/A–Z range. Extended ASCII and multi-byte character sets will not be transformed correctly. For true multi-byte safety there are `mbstring` equivalents:

```
$quote = "\u{15e}\u{fc}phe ve belirsizlik i\u{e7}ermeyen kat\u{131}
kurallar talep ediyoruz!";
$lower = mb_strtolower($quote);
$upper = mb_strtoupper($quote);

print $quote . PHP_EOL;
print $lower . PHP_EOL;
print $upper . PHP_EOL;
```

```
Output:
Şüphe ve belirsizlik içermeyen katı kurallar talep ediyoruz!
şüphe ve belirsizlik içermeyen katı kurallar talep ediyoruz!
ŞÜPHE VE BELIRSIZLIK IÇERMEYEN KATI KURALLAR TALEP EDIYORUZ!
```

But we still have a problem. For those of you that don't speak Turkish, the example above highlights a potential issue with these two functions. `mb_strtoupper()` (and its counterpart) is not locale-aware: in the Turkish alphabet, the correct capitalization of `i` should be `İ` (`içermeyen` should have been transformed to `İÇERMEYEN`, and so on). This isn't a bug as such; it is simply following (one of) the Unicode specifications for