(More) `mbstring` Functions

The following `mbstring` functions will be featured in this section:

Table 8-22. *Featured `mbstring` functions*

`mb_check_encoding()`	Validate encoding of a string
`mb_convert_encoding()`	Convert a string to a different encoding
`mb_convert_kana()`	Japanese-language-only alphabet conversion
`mb_convert_variables()`	Convert encoding of multiple strings in one call
`mb_detect_encoding()`	Attempt to detect probable encoding of a string
`mb_detect_order()`	Control the order in which to detect character encoding
`mb_encoding_aliases()`	Get aliases for encoding type (if known)
`mb_get_info()`	Returns internal configuration of mbstring module
`mb_internal_encoding()`	Get/set PHP's internal character encoding
`mb_list_encodings()`	Get list of all known encodings
`mb_scrub()`	Clean up a malformed string, replaces invalid sequences with a ? character
`mb_substitute_character()`	Get/set the substitution for invalid sequences

As in the previous section, these functions will be (roughly) grouped by functionality: info and settings, data inspection, and data conversion.

Info and Settings

`mbstring` offers utility functions for obtaining information about system encoding settings, information about the string data being processed, and for controlling encoding program-wide.

`mb_get_info()`

For a full and complete picture of how `mbstring` will behave, we have `mb_get_info()`, which returns all of the settings we looked at the start of the section.