```
$ curl -v http://localhost:8080
*   Trying 127.0.0.1:8080...
* Connected to localhost (127.0.0.1) port 8080 (#0)
> GET / HTTP/1.1
> Host: localhost:8080
> User-Agent: curl/8.1.2
> Accept: */*
>
< HTTP/1.1 200 OK
< Host: localhost:8080
< Date: Sun, 22 Oct 2023 16:06:38 GMT
< Connection: close
< X-Powered-By: PHP/8.4.6
< Content-type: text/html; charset=UTF-8
<
* Closing connection 0
<pre>Hello from php-fpm!</pre><pre>We are running under cli-server
SAPI</pre>
```

As we can see from the end of the output, the SAPI reported by PHP has changed to `cli-server`. Using `curl -v` means we get verbose output and therefore we can see that in addition to the output of our simple program we also get some HTTP response headers (`Host: localhost:8080`, `X-Powered-By: PHP/8.4.6`, and so on). This is a function of the web-server SAPIs: they will automatically return certain headers in addition to the output of your program. Full details can be found in Chapter 11, "Programming for the Internet."

If you glance at the terminal in which the PHP server is running, there will be some output logged along the lines of the following…

```
PHP 8.2.10 Development Server (http://localhost:8080) started
[::1]:36978 Accepted
[::1]:36978 [200]: GET /
[::1]:36978 Closing
```

… which is of course very useful for debugging purposes.