```
mb_internal_encoding("UTF-16BE");
print bin2hex(mb_convert_encoding($rawUTF16BE, to_encoding: 'UTF-8')) .
PHP_EOL;
```

```
Output:
UTF-8
00480065006c006c006f
48656c6c6f
```

With internal encoding set to UTF-8, the `$rawUTF16BE` string remains unchanged because the input is assumed to be UTF-8. When internal encoding is changed to `UTF16-BE`, `mb_convert_encoding()` now knows it should map the bytes to `UTF-8` encoding, as shown in the final line of output.

mb_detect_order()

Some `mbstring` functions will examine input strings and attempt to guess the encoding. This is not the preferred method of managing encoding and transforms; the layers above and below your application should know how text data is encoded (and exercise control where possible). Nevertheless, it is sometimes necessary to guess, and there is also the use-case of verifying correct encoding for security purposes. `mb_detect_order()` will report the order in which encoding types are tested against input data and allow the order to be defined at runtime:

```
print_r(mb_detect_order()) . PHP_EOL;
print mb_detect_encoding("Single bytes") . PHP_EOL;
print mb_detect_encoding("\u{141}");
```

```
Output:
Array
(
    [0] => ASCII
    [1] => UTF-8
)
ASCII
UTF-8
```