The full list of these "non-printing" escapes is as follows:

Table 8-25. *PCRE non-printing regex escape sequences*

Escape sequence	ASCII character
\a	Alarm (BEL *0x07*)
\cx	Control character (allows representation of first 26 ASCII bytes)
\e	Escape (ESC *0x1B*)
\f	Formfeed (FF *0x0C*)
\n	Newline (NL *0x0A*)
\p{xx}	Character with Unicode property
\P{xx}	Character without Unicode property
\r	Carriage return (CR *0x0D*)
\R	Represent multiple forms of line break (\n, \r, \r\n)
\t	Horizontal tab (TAB *0x09*)
\xhh	Hexadecimal byte value, e.g., \x0A = n
\ddd	Octal escape up to three digits, e.g., \012 = \n

Some of these forms require explanation (or warnings). The control character escape \cx, where x is any ASCII alphabet character, produces a value that maps to one of the ASCII characters *0x01* to *0x1A* (in other words, 1–26). Brace yourself: it does this by calculating the ordinal value of the letter (in the ASCII codepage) modulo 32. If we take the letter J, for example, its ASCII ordinal value is *74*, *74 % 32* is *10*, and the tenth ASCII character is the newline character *0x0A*. Furthermore, there is no difference between upper and lower case, because each ASCII Latin upper/lowercase mapping is exactly *32* codepoints in distance – A ordinal position is *65*, a is *97*, B/b is *66*/*98*, etc. The output of the following code is int(1) for both (\cj and \cJ are equivalent):

```
var_dump(preg_match_all('/o\cjw/', $text));
var_dump(preg_match_all('/o\cJw/', $text));
```

```
Output:
int(1)
int(1)
```