```
$cyrillic = "\u{421}\u{421}\u{421}\u{420}";
$pattern = '/\p{Cyrillic}/u'; // note the 'u' modifier
print $cyrillic . PHP_EOL;
var_dump(preg_match_all($pattern, $cyrillic));
```

```
Output:
CCCP
int(4)
```

It's important to note the use of the u modifier here: this tells the PCRE engine to evaluate the sample as UTF-8 encoded text. The short-form Unicode properties will work without it, but it's a good idea to be explicit. PHP supports a wide variety of script names that can be used in conjunction with the \p and \P modifiers; `Arabic`, `Braille`, `Cuneiform`… all the way to `Vai` (not Steve!) and `Yi`. Some more useful property codes are given in the table below but be aware this is not exhaustive. The full list of Unicode property escapes in PHP is available at https://www.php.net/manual/en/regexp.reference.unicode.php

Table 8-26. *Unicode property codes*

`L`	Letter: includes all `Ll`, `Lu`, `Lt` etc.
`Ll`	Letter: lowercase
`Lo`	Letter, other: e.g., `CJK Unified Ideographs`
`Lt`	Letter: title case
`Lu`	Letter: uppercase
`N`	Number
`Nd`	Number, decimal
`Nl`	Number, letter: e.g., runic, Roman numerals
`P`	Punctuation
`Sc`	Currency symbol: e.g., $, £, €
`Z`	Separator: e.g., newline, space