The full list of mb_ereg* functions is as follows:

Table 8-37. *mbstring regex functions*

mb_ereg() mb_eregi()	Non-global pattern match, with/without case sensitivity, optional results array
mb_ereg_match()	Anchored pattern match with various options, does not support a results array
mb_ereg_replace() mb_eregi_replace()	Similar to preg_replace, but no support for input arrays
mb_ereg_replace_callback()	Callback variant of mb_ereg_replace(), etc.
mb_ereg_search()	Performs search on string set by mb_ereg_search_init()
mb_ereg_search_getpos()	Used with mb_ereg_search() to get byte position for next match
mb_ereg_search_getregs()	Get result of last match from mb_ereg_search()
mb_ereg_search_init()	Initialise sample string for mb_ereg_search()
mb_ereg_search_pos()	Get position and length of last match from mb_ereg_search()
mb_ereg_search_regs()	Get matched part of expression for mb_ereg_search()
mb_ereg_search_setpos()	Set starting byte for mb_ereg_search()
mb_regex_encoding()	Set internal encoding scheme for mb_ereg*() functions
mb_regex_set_options()	Control behavior of mb_ereg*

mb_ereg_match(), mb_ereg_replace(), mb_eregi_replace(), mb_ereg_replace_callback()

This quartet of functions is more or less identical to their preg_* equivalents. mb_ereg_match() behaves just like preg_match() but does not support the $matches by-reference parameter, and the pattern is always implicitly anchored to the start of the sample. It does, however, allow the passing of options and has multiple syntax modes (so it is not limited to PCRE, although PCRE is expressive enough to get just about any job done that I've ever come across in the wild). We'll examine those options and modes in a moment when we get to mb_ereg_set_options(). It also returns bool(true) on a successful match, rather than the int(1) of preg_match().