```
// $text = <<<EOS ...
// Reinitialise
mb_ereg_search_init($text);

mb_ereg_search('^\w+:\s');

mb_ereg_search_pos('[^,\r\n]+');
mb_ereg_search_getregs();

print_r(mb_ereg_search_pos('[\r\n]+'));
mb_ereg_search_setpos(0);
print_r(mb_ereg_search_pos('^\w+:\s'));

Output:
Array
(
    [0] => 21
    [1] => 1
)
Array
(
    [0] => 0
    [1] => 9
)
```

The pattern `[\r\n]+` matches one byte at offset twenty-one; at this point, we're about halfway through the sample. By calling `mb_ereg_search_setpos(0)`, we begin matching from the very start of the sample again, and we're able to get a nine-byte match from `^\w+:\s` (note the `^` anchoring character).

### mb_regex_set_options()

As previously stated, it is possible with all of the `mb_ereg*` functions to supply a string of options or even change the dialect of regex in use (you never know, you might need to). Here's a quick example of how we can change the behavior of `mb_ereg_match()` by supplying an option parameter:

```
var_dump(mb_ereg_match('\x{141}\w+', "\u{142}ukasz"));
var_dump(mb_ereg_match('\x{141}\w+', "\u{142}ukasz", 'i'));
```