There we have it, pre-processed hypertext! The only PHP in the file above is contained between opening and closing tags:

```
<?php
    print "<p>This paragraph was created with PHP SAPI: <pre>" . PHP_SAPI .
    "</pre></p>";
?>
```

It's a simple `print` statement, much like those used earlier in the chapter. Let's create a similar file, but this time it'll be pure PHP, and we're going to use something called HEREDOC, which is a programmer-friendly way of creating multi-line chunks of text within code.

Pure PHP Files

Create a new file, `index2.php` in the same location as `index.php` with the following contents (remember to include an opening tag at the start):

```
$sapi = PHP_SAPI;

print <<<HTML
<!DOCTYPE html>
<html>
<head>
    <title>Old school PHP</title>
</head>
<body>
    <p>This entire document was created with PHP SAPI: <pre>{$sapi}
    </pre></p>
</body>
</html>
HTML;
```

This is a slightly more complex program; it has two statements. The first – `$sapi = PHP_SAPI;` – assigns the value of `PHP_SAPI` to a variable because we can't use constants in the next statement, which is use something called `HEREDOC` syntax – `print <<<HTML ...`. This form of statement takes everything between the `<<<HTML` and `HTML;` lines and treats it as text. HEREDOC allows variables to be interpolated into the text, which is