```
    ->format(DateTime::COOKIE) . PHP_EOL;

print $dt->add(new DateInterval("P3DT5H"))
    ->format(DateTime::COOKIE);

Output:
Sunday, 01-Sep-2024 05:10:20 GMT+0000
Wednesday, 04-Sep-2024 05:00:00 GMT+0000
```

`DateInterval` instances are also returned from the `DateTime::diff()` function when evaluating two different date/time values. The following example demonstrates both the use of `diff()` and an alternative way of creating `DateTime` instances:

```
$bellRiots = DateTime::createFromFormat(
    'Y-m-d H:i:s O',
    '2024-09-01 00:00:00 PST'
);
print $bellRiots->format(DateTime::COOKIE) . PHP_EOL;

$retakeSanctuary = DateTime::createFromFormat(
    'Y-m-d H:i:s O',
    '2024-09-03 05:00:00 PST'
);
print $retakeSanctuary->format(DateTime::COOKIE) . PHP_EOL;

$dti = $bellRiots->diff($retakeSanctuary);
print "Diff is {$dti->d} days, {$dti->h} hours";

Output:
Sunday, 01-Sep-2024 00:00:00 PST
Tuesday, 03-Sep-2024 05:00:00 PST
Diff is 2 days, 5 hours
```

Notice that we can access the public properties `$dti->d` and `$dit->h`. The interval object exposes the properties `y`, `m`, `d`, `h`, `i`, `s`, and `f`, which correspond to years, months, days, hours, seconds, and microseconds (as the `float` type, expressing fractions of a second). The public properties `invert` (`1` if the interval is negative, `0` if positive), `days` (total number of full days in the interval, *only* if the object was created by