The most reliable way to get the request headers is via the $_SERVER superglobal. Put the following code into a file index.php and serve with the container of your choice. You could carry on with the nginx container we just built or take it down and run another cli-server. It's up to you.

```
// index.php
var_dump($_SERVER);
```

Assuming you're running your server on TCP 8080, try the following curl command:

```
$ curl http://localhost:8080/index.php
array(19) {
  ["DOCUMENT_ROOT"]=>
  string(14) "/usr/src/myapp"
  ["REMOTE_ADDR"]=>
  string(10) "172.17.0.1"
  ...
  ["HTTP_HOST"]=>
  string(14) "localhost:8080"
  ["HTTP_USER_AGENT"]=>
  string(10) "curl/8.7.1"
  ["HTTP_ACCEPT"]=>
  string(3) "*/*"
  ...
```

Pay attention to all of the array keys starting with HTTP_ … These are the header fields sent in the request. Each field name is capitalized, prepended with HTTP_, and any dashes in the field names are replaced with underscores (thus User-Agent: becomes HTTP_USER_AGENT, and so on). The value of the field is mapped to the key in $_SERVER. We can test this by injecting our own headers with a -H 'Header: value' option in the curl request:

```
$ curl -H 'X-Custom-Header: some value' http://localhost:8080/index.php
  ...
  ["HTTP_X_CUSTOM_HEADER"]=>
  string(10) "some value"
  ...
```