PHP makes request cookies available via the `$_COOKIE` superglobal (make sure the `variables_order` ini directive contains a "C" in its value). Let's have a quick demo:

```
// index.php
var_dump($_COOKIE);
```

The curl binary allows us to send multiple cookie pairs with the `-b` switch:

```
$ curl -b cat=miaow -b dog=woof http://localhost:8080/index.php
array(2) {
  ["cat"]=>
  string(5) "miaow"
  ["dog"]=>
  string(4) "woof"
}
```

Here's another way to do it, using the `Cookie:` header:

```
$ curl -H 'Cookie: cat=miaow; dog=woof' http://localhost:8080/index.php
```

To set cookies in the response, use the `setcookie()` and `setrawcookie()` functions:

```
// index.php
setcookie(
    name: 'flavour',
    value: 'choc chip obvs'
);
print "Thanks for visiting!\n";
```

To see the effect of setting a cookie, we need to see the response headers, which requires running curl in verbose mode with `-v`:

```
$ curl -v http://localhost:8080/index.php
* Host localhost:8080 was resolved.
* IPv6: ::1
* IPv4: 127.0.0.1
*   Trying [::1]:8080...
* Connected to localhost (::1) port 8080
> GET /index.php HTTP/1.1
> Host: localhost:8080
```