```
> User-Agent: curl/8.7.1
> Accept: */*
>
* Request completely sent off
< HTTP/1.1 200 OK
< Host: localhost:8080
< Date: Tue, 08 Jul 2025 15:32:00 GMT
< Connection: close
< X-Powered-By: PHP/8.4.6
< Set-Cookie: flavour=choc%20chip%20obvs
< Content-type: text/html; charset=UTF-8
<
Thanks for visiting!
* Closing connection
```

Don't be alarmed if the formatting of your output varies slightly from that given above; different versions of cURL, different platforms… such is the nature of open-source software. The important details will still line up: the header names and values should be identical. Note that the `Set-Cookie:` header has been encoded, with spaces transformed to the character sequence `%20`. This specific encoding format is known as "url encoding," which turns certain illegal characters in URLs into numeric sequences prepended with a % symbol. We'll be looking at common encoding methods in a later section of this chapter when we examine security concerns.

The original cookie specification from Netscape (shout out to anyone old enough to remember Navigator) stated that space, comma, and semicolon were illegal characters, and although most modern systems will handle spaces in cookie data, it's a good idea to encode them. Should you need it, PHP's `setrawcookie()` does away with the encoding. Remember that cookies are set by headers and therefore cannot be sent if even a single byte of the response body has been sent. In the example above we created a very simple key/value cookie with no other information, and we can see in the `Set-Cookie:` header there is no expiry timestamp, so this cookie is session-only. If we add an integer timestamp to the `setcookie()` call, then we can add a UTC timestamp, which will have the effect of persisting the cookie:

```
// index.php
setcookie(
    name: 'flavour',
```