return is `false` because `/etc/passwd` was most definitely NOT uploaded during this request, and you should probably leave it alone!). Next we call `move_uploaded_file()` with a second argument to specify where we'd like to move the upload to – remember the `__DIR__` constant maps to the directory of the current source code file – which has the effect of moving the upload from `/tmp/` to the same directory as our `index.php` file and renames it to `uploaded.jpg` in the process. Finally, another call to `is_uploaded_file()` confirms the file move; it now returns `false` because the temporary file no longer exists. We can confirm with a quick check of the filesystem:

```
$ ls
index.php   uploaded.jpg
```

In a production system you will of course have far more secure settings in place; it is unlikely the owning account of the PHP process will have write access to the source code directory, nor should your code (or indeed the web server) be able to access somewhere like `/etc`. Also, bear in mind that `POST` requests are not idempotent, and multiple identical requests should create a new file every time (no matter if it's the same file each time). Our simple script above behaves more like a `PUT` upload (which we'll look at in a moment) because the result is the same `uploaded.jpg` file every time. In a real-world situation, you would probably want to include some unique identifier in the filename.

One more thing to look at for multipart POST data: as you might recall, I said it is possible to mix different content types with a `multipart/form-data` POST request; indeed, this is what this media type is designed for. Remember that each content section (delimited by the boundary string) can have its own `Content-Type:` and `Content-Disposition:` headers, so you can upload a mix of file data and more conventional POST encoded data, or even multiple files in one request. Let's have a quick look at how that works from PHP's perspective. The code we'll need in our `index.php` is as follows…

```
// index.php
var_dump($_FILES);
var_dump($_POST);
```

… and our curl command is:

```
$ curl -F 'file=@./random.jpg' \
  -F 'animals[cat]=jess&humans[]=anna&humans[]=paul' \
  http://localhost:8080/index.php
```