Table 11-6. *PHP session handling functions*

`session_abort()`	Discard all changes made this request to `$_SESSION` and end the session.
`session_cache_expire()`	Controls `Expires:` and `max-age` directive of `Cache-Control:` headers
`session_cache_limiter()`	Controls caching behavior of client and/or proxies
`session_commit()`	Alias of `session_write_close()`
`session_create_id()`	Create a new (collision free) session ID string
`session_gc()`	Trigger session garbage collection
`session_id()`	Get/set the current session ID
`session_module_name()`	Get/set the session module – file/Redis/memcached, etc.
`session_regenerate_id()`	Generate a new ID for current session, optionally delete old session
`session_set_cookie_params()`	Control cookie parameters (expiry, max-age, same-site, etc.)
`session_set_save_handler()`	Replace default instance of `SessionHandler` with a modified instance
`session_start()`	Begin/resume a session
`session_unset()`	Equivalent to `$_SESSION = [];`
`session_write_close()`	Write `$_SESSION` to storage and end the current session

Full information for all session functions can be found at https://www.php.net/manual/en/ref.session.php and all ini directives are documented at https://www.php.net/manual/en/session.configuration.php

Modifying HTML (and XML)

Without further ado, it's time for the main event, the reason why PHP was invented! The acronym PHP originally stood for "Personal Home Page," then revised/retconned to the recursive "PHP Hypertext Preprocessor." Either way, the message is clear: PHP exists to process HTML. It is certainly my favorite back-end language for the task. Just as PHP has a large assortment of tools for handling HTTP requests, it is also loaded with functions