For example, you might want to have bold text for `h1` elements that have a `main` ancestor:

```
main h1 {
    font-weight: bold;
}
```

Popularizing the idea of using CSS selector syntax as a means to quickly fly around a DOM structure can be credited to the venerable `jQuery` library (inspired by the earlier `cssLibrary`), which made JavaScript a far nicer place to work – especially for back-end duffers like me – way back in the mists of time (2006, to be precise). Of particular note was its core traversal mechanism, where you simply called the global jQuery object as a function with a CSS selector string as an argument. This returned one or more references to matching DOM elements that could then be messed about with to your heart's content. The idea was so popular that it eventually made its way into JavaScript standards as the Selectors API (around 2013). An exhaustive list of jQuery functionality that has found its way into modern JavaScript can be found here: https://youmightnotneedjquery.com/

PHP has for a while had third-party libraries that implement the same feature – Symfony's DomCrawler component is a good example https://symfony.com/doc/current/components/dom_crawler.html – and now PHP 8.4 gives us native support. Time for a quick demo.

```
$html5 = <<<EOS
<!DOCTYPE html>
<html>
  <head>
    <meta charset="utf-8" />
    <title>HTML5 is lovely</title>
  </head>
  <body>
    <header>Page header</header>
    <main class="main-content">
      <p class="large">Para One</p>
      <p class="small">Para Two</p>
      <p class="small">Para Three</p>
    </main>
    <footer>Page footer</footer>
```