```
Output:
Parent:
main
```

Other useful (to us, in PHP world) positional pseudo-classes are:

Table 11-22. *CSS pseudo-classes*

Pseudo-class	XPath Equivalent
`:first-child`	`/*[1]`
`:last-child`	`/*[last()]`
`:nth-child(n)`	`/*[n]`
`:first-of-type`	`/node[1]` or `*[1][name() = "node"]`
`:last-of-type`	`/node[last()]` or `*[last()][name() = "node"]`
`:nth-of-type(n)`	`/node[n]` or `*[n][name() = "node"]`
`:only-child` or `:first-child:last-child`	`[count() = 1]`

That will do to get you started with CSS selectors, and like before, I highly recommend the MDN CSS learning guides, starting with https://developer.mozilla.org/en-US/docs/Web/CSS/CSS_selectors/Selector_structure. For the rest of this section I'll use `Dom\XPath` and `Dom\HTMLDocument::querySelectorAll()` interchangeably so you can get used to seeing both.

DOM Modification and Output

Let's take a moment and review what we've learned. HTML is a markup language (a specialized form of XML, in fact) that allows you to create a document that mixes literal text with metadata (in the form of tags such as `<head>`, `<body>`, `<div>`, and so on) to form a data structure called a DOM. The structure is a tree, with `html` as its root element, which must have both `head` and `body` child elements. The `head` element contains at least a `title` element and usually other children like `meta` and `link`. These `head` elements allow you to do things like define document metadata like character encoding and