examination of all things HTTP when discussing URL encoding (remember we needed to URL encode POST data to change meta-characters that would otherwise change the structure of the decoded data). The problem we have here is very similar: when generating HTML from a template, what if the data we're injecting into the template also contains HTML? Why could it be a problem?

Let's start with a simple example. Imagine that we're handling a form POST request, and somewhere in that form data is some markup; we'll simulate that with the hard-coded `$postData` array. This exercise intentionally does not use Twig in order to demonstrate one of the reasons why Twig (or something like it) is a Jolly Good Idea. Make a new `index.php` file and put this as the first code:

```
// index.php
$postData = [
    'title' => 'Lulzsec',
    'name' => 'Mr Trustworthy',
    'age' => 49,
    'occupation' => '<script>window.alert("I control the browser now.")
    </script>',
];
```

With our data in place, we'll create a naive string-interpolating "template" similar to the `my-first.html.twig` template from earlier. Add the following lines below the `$postData` statement:

```
print <<<EOS
<!DOCTYPE html>
<html>
  <head>
    <title>{$postData['title']}</title>
  </head>
  <body>
    <h1>{$postData['name']}</h1>
    <p>Age: {$postData['age']}</p>
    <p>Occupation: {$postData['occupation']}</p>
  </body>
</html>
EOS;
```