... because by default Twig will filter any data that is placed into your template with the {{ }} syntax. The `script` element has been encoded so that the browser won't parse the script tags; you can view the page source to see how:

```
<p>Occupation: &lt;script&gt;window.alert(&quot;I control the browser
now.&quot;)&lt;/script&gt;</p>
```

This particular type of encoding is *html entity encoding*, which itself comes in two flavors: character (or name) encoding and numeric encoding. They exist because you might want to render text like `<script>` in a page (and not have the contents parsed as JavaScript), and some exist from the olden days when it was easier to rely on encoding for certain characters than trust the myriad of ISO extended ASCII character encodings. The following table gives examples of some common ones (notice that the punctuation meta-character numeric entity values correspond to their ASCII code page decimal values):

Table 11-26. *HTML entity encoding*

Meta-character	Name encoding	Numeric encoding
<	<	<
>	>	>
&	&	&
"	&quot	"
™	™	™

We'll come back to the nuts and bolts of entity encoding for later, once we're done with Twig.

Controlling Escaping

The default escaping strategy for Twig is to treat everything as HTML, and it is enabled by default. To turn this feature off, use the `autoescape` config key when the `Twig\Environment` object is instantiated. Change the previous example so that the `Twig\Environment` boilerplate has an array as its second constructor argument. The array needs to contain an `autoescape` key, like this: