```
    <li>Paul</li>
  </ul>
```

Twig Operators and Expressions

The example above uses very plain expressions to demonstrate the {% if %} and {% for %} tags, but Twig supports expressions in {% %} tags and {{ }} output. As you might expect, these are broadly equivalent to PHP expressions but with a layer of abstraction/simplification applied. You can perform all the usual mathematical, logical, and comparison operations, and Twig (in the more recent releases) even supports new PHP functionality such as ?? null-coalesce, and ... spread. You can even make use of => arrow function notation (tread carefully). We're now going to look at the building blocks of Twig expressions, which start out as more or less directly equivalent to PHP's underlying implementations, with some complex (but common) operations abstracted to simple word-based statements rather than falling back to having to write out small functions or blocks of code.

Literals

Table 11-30. *Twig literal value syntax*

`"abc" '123'`	Any character(s) wrapped in quotes is a string
`"string #{EXPR} interpolation"`	#{} interpolates EXPR into double-quote strings only
`123 -123.4 1_234_567`	Integers, floats, underscores permitted for readability
`\" \'`	Backslash escape for strings containing quote characters
`\r \n \t` etc.	ASCII backslash escapes ()
`\0 - \377`	Octal ASCII escape values
`['foo', 'bar']`	Array (or "sequence")
`{'cat': 'Jess'} {humans: ['Anna', 'Paul']}`	Associative array (or "mapping"), quoting keys is optional
`true false`	Booleans
`null`	null