```
$ curl -v http://localhost:8080/index.php
<div>
    Anna, Paul... and Jess the cat. Purr purr.
</div>
```

Here the addcat filter is modified so that the template context is available when the callable executes; you can see the differences in the filter object construction. The needs_context option tells the TwigFilter object to pass the context array when the filter is used in a template and the underlying callable is invoked, demonstrated by creating a simple context variable when we make the ::render() call. Table 11-40 contains a synopsis of useful options and their corresponding effects:

Table 11-40. *TwigFilter class constructor options*

Option	Effect
'needs_charset' => true	Passes (string $charset, $input) to callable
'needs_context' => true	Passes (array $context, $input)
'needs_environment' => true	Passes (\Twig\TwigEnvironment $twig, $input)
'pre_escape' => 'html'	Applies html escaping (or any of the others) to input
'is_safe' => 'html'	Suppresses html autoescaping (or any of the others) of output

In cases where multiple options are required that would result in callable parameter changes, the arguments are supplied in the order the options are defined: ['needs_context' => true, 'needs_charset' => true] would result in callable parameters (array $context, string $charset, $input).

Adding a Function

Adding a function to templates is a very similar process; the main difference is their use inside templates, and that function extensions don't support pre_escape and preserves_safety options.

```
// index.php
require_once __DIR__ . '/vendor/autoload.php';
```