mb_substr_count(), 470–474
mb_trim(), 509, 511
mb_ucfirst(), 501, 502
md5(), 520, 521
md5_file(), 520, 521
Media types, 703
Members, 287
Metacharacters, 564, 570, 843
metaphone(), 457
microtime(), 634, 635
MIME types, *see* Media types
Mixed (super) type, 119, 120
Mixing call styles, 132–134
mktime(), 630–633
Model-view-controller (MVC), 806, 837
Modular decomposition, 642
Modularity, 286
move_uploaded_file() function, 710, 711
Multi-byte encodings, 477
Multi-byte safety, 441–444, 450
Multidimensional arrays, 212–215, 227, 228, 253, 280–282
MVC, *see* Model-view-controller (MVC)

## N

Named function, 100, 101, 138
Named parameters, 129–132
Namespaced functions
  calling functions, 155, 156
  collision(), 154
  example, 154
  global, 155
  multiple statements, 155
  qualified calls, 156, 157
  scope, 158, 159
  usage, 157
Namespacing, 13, 198, 341–343, 779–782
networks.internal node, 24
Network time protocol (NTP), 607, 608
Nginx, 23–27
nl2br(), 497, 498
Non-boolean values, 164
Nowdoc syntax, 419
NTP, *see* Network time protocol (NTP)
Nullable types, 113
Null coalescing operator, 184, 185
Null safe operator, 185, 186
number_format(), 498
Number systems
  bases, 372
  built-in functionality, 372
  converting bases, 374, 375
  defined, 372
  formatting, 375, 376
  non-decimal integer literals, 372, 373
  scientific notation, 374
Number types, 80
Numerical strings, 405–408
Numeric encoding, 817

## O

Object functions, 352
Object instance, 354
Object model, 639
Object-oriented design (OOD), 321, 640
Object-oriented exception model, 187
Object-oriented programming (OOP), 159, 736, 738
  advantages, 286
  classes, 290–303
  cloned objects, 289, 290