Uniform resource locators (URLs) (*cont.*)
fragment/anchor, 680
path, 681
query, 681
resource path, 700
router, 693
routing, 727
scheme, 680
schemes, 58
Union types, 114–116
Universal Coded Character Set (UCS), 426
Unix domain socket, 66
Unix epoch, 606, 607
Unpacked arguments, 132
unserialize(), 734
unset() function, 83
URLs, *see* Uniform resource locators (URLs)
useQuoteBot() function, 314
User-defined types, 110
useVehicle() functions, 656
UTC, *see* Coordinated Universal Time (UTC)
UTF-1, 428
UTF-8, 430, 432–434, 436
UTF-16, 427, 428, 472
UTF-32, 427
Utility functions, 384, 386, 443

## V

Variables
echo keyword, 82
functions, 144–146
initialization, 87
legal names, 83, 84
string literal, 82
symbolic name, 82
Variable variables, 95, 96
Variadic function, 125–129
Variadic parameters, 127
vfprintf(), 498
Virtual machine, 12
Visitor pattern, 674
vprintf(), 498

## W

W3C, *see* World Wide Web Consortium (W3C)
Web browser, 678
Web development, 371, 427
Web Hypertext Application Technology Working Group (WHATWG), 747
Web server integration, 690
Apache module, 30
built-in functionality, 23
built-in web-server, 27–29
Nginx, 23–27
WHATWG, *see* Web Hypertext Application Technology Working Group (WHATWG)
Whole string, 514, 515
Wi-Fi data, 540
Windows Subsystem for Linux (WSL), 11
wordwrap(), 496, 497
World Wide Web Consortium (W3C), 748
wrongFunc(), 146
WSL, *see* Windows Subsystem for Linux (WSL)

## X, Y

XCode command line tools, 8
XPath