```
+---------+-------------+------+-----+---------+----------------+
| Field   | Type        | Null | Key | Default | Extra          |
+---------+-------------+------+-----+---------+----------------+
| id      | int(10)     | NO   | PRI | NULL    | auto_increment |
| message | varchar(255)| NO   |     | NULL    |                |
+---------+-------------+------+-----+---------+----------------+
2 rows in set (0.002 sec)
```

Next we can add some data to the table…

```
$pdo->exec("INSERT INTO test(`message`) VALUES('some text')");
$pdo->exec("INSERT INTO test(`message`) VALUES('some more text')");
$pdo->exec("INSERT INTO test(`message`) VALUES('even more text')");
```

… and confirm the results in the `mariadb` cli:

```
MariaDB [testdb]> SELECT * FROM test;
+----+----------------+
| id | message        |
+----+----------------+
|  1 | some text      |
|  2 | some more text |
|  3 | even more text |
+----+----------------+
3 rows in set (0.001 sec)
```

Selecting Results

SQL is a declarative language: rather than issue step-by-step instructions, instead the desired results are described, and the query engine makes the internal decisions about how to create the result set. When we want to retrieve a set of data from the DB, we need to use a `SELECT` statement; the method for doing this with `PDO` is a little different from what we've seen so far. `$pdo->exec()` simply runs the SQL in its argument and will only return a count of affected rows. To actually get data, we use `$pdo->query()`: