```
use Illuminate\Support\Facades\Blade;
return Blade::render('Welcome, {{ $name }}', ['name' =>
'ABC']);
```

By writing the inline Blade templates to the **`storage/framework/views`** directory, Laravel renders them. You may provide the function the **`deleteCachedView`** argument if you want Laravel to delete these temporary files after rendering the Blade template:

```
return Blade::render(
  'Welcome, {{ $name }}',
  ['name' => 'ABC'],
  deleteCachedView: true
);
```

Rendering Blade Fragments

It may occasionally be necessary to just return a piece of a Blade template within your HTTP response when utilizing frontend frameworks like Turbo and htmx. You may achieve it by using blade **fragments**. Place a section of your Blade template inside the **`@fragment`** and **`@endfragment`** directives to get started:

```
@fragment('employee-list')
  <ul>
    @foreach ($employees as $employee)
      <li>{{ $employee->name }}</li>
    @endforeach
  </ul>
@endfragment
```

Then, you can use the **`fragment`** method to specify that just the given fragment should be included in the outgoing HTTP response when displaying the view that makes use of this template:

```
return view('homepage', ['employee' => $employees])-
>fragment('employee-list');
```

By using the **`fragmentIf`** method, you may conditionally return a view fragment based on a specified condition. In such a case, the whole view will be returned:

```
return view('homepage', ['employees' => $employees])
```