```
  ->fragmentIf($request->hasHeader('HX-Request'), 'employee-
  list');
```

The two methods – **`fragments`** and **`fragmentIf`** – enable to return multiple view fragments in the response. For example:

```
view('homepage', ['employees' => $employee])
  ->fragments(['employee-list', 'task-list']);
view('homepage' ['employees' => $employees])
  ->fragmentsIf(
    $request->hasHeader('HX-Request'),
    ['employee-list', 'task-list']
  );
```

Conclusion

In this chapter, we explored the essential components of Laravel web development - Controllers and Blade templates. Controllers are important in the MVC architecture as they group the functionality of routes. We discussed how to create controllers using the Artisan command and how to manage actions for specific resources.

In the next chapter, we will delve into Eloquent and Query Builder in Laravel, which are essential for database operations. The upcoming chapter will also cover how to perform common Eloquent operations applied to the database using query builders.

Points to Remember

- Resource Controllers provide a convenient way to handle CRUD operations for multiple resources in an application, which is generated using the **`make:controller`** command. Routes are defined for resource controllers.
- Constructor injection and method injection, where dependencies are automatically resolved and injected into controller instances, providing clean and organized code.
- Redirects in Laravel are responses that send the user to a different URL. There are various ways to create redirects, including the Redirect Helper, named routes, and controller actions. Additionally, flashing