You can use the **`lockForUpdate`** method on a query to **lock for update** on a **`SELECT`** statement:

```
DB::table('employees')->where('votes', '>', 140)-
>lockForUpdate()->get();
```

Caching Queries

Using the **`remember or rememberForever`** technique, you can conveniently cache a query's results:

```
$value = Cache::rememberForever('employees', function () {
  return DB::table('employees')->get();
});
```

This will retrieve it from the cache if it exists or store it forever if it does not exist.

Eloquent Operations

Eloquent, an object-relational mapper (ORM) that makes working with your database fun, is a component of Laravel. Each database table in Eloquent has a corresponding **Model** that is used to communicate with the table. Eloquent models allow you to insert, edit, and delete records from the database table in addition to fetching them.

Model Classes

Let's start by building an Eloquent model. The **`Illuminate\Database\Eloquent\Model`** class is generally extended with models, which are typically located in the **`app\Models`** directory. You could use the model Artisan command **`make:model`** to create a new model:

```
php artisan make:model Office
```

Use the **`--migration`** or **`-m`** option to generate a database model:

```
php artisan make:model Office –-migration
```

When creating a model, you may also create different classes such as factories, seeders, policies, controllers, and form requests. Additionally, by combining these choices, it is possible to create numerous classes at once:

```
# Generate a model and a OfficeFactory class…
```