Keep in mind that the following middleware groups are automatically applied to the routes in your relevant **web** and **api** route files by your application's **App\Providers\RouteServiceProvider** service provider:

```
/**
 * The application's route middleware groups.
 *
 * @var array
 */
protected $middlewareGroups = [
 'web' => [
  \App\Http\Middleware\EncryptCookies::class,
  \Illuminate\Cookie\Middleware\AddQueuedCookiesToResponse::cla
  ss,
  \Illuminate\Session\Middleware\StartSession::class,
  \Illuminate\View\Middleware\ShareErrorsFromSession::class,
  \App\Http\Middleware\VerifyCsrfToken::class,
  \Illuminate\Routing\Middleware\SubstituteBindings::class,
 ],
 'api' => [
  \Illuminate\Routing\Middleware\ThrottleRequests::class.':api'
  ,
  \Illuminate\Routing\Middleware\SubstituteBindings::class,
 ],
];
```

In order to assign the middleware groups, the syntax remains similar to that of linking middleware to the routes and controllers. This helps in enabling the logic in our Laravel application code and also attaching the middleware to a route.

```
Route::get('/', function () {
 // Code Logic
})->middleware('web');
Route::middleware(['web'])->group(function () {
  // Code Logic
});
```

The **App\Providers\RouteServiceProvider** automatically applies the **web** and **api** middleware groups to the respective **routes/web.php** and