```
  // Code Logic
})->middleware('auth:api-customers');
```

Access Token

Your application's API users should provide their access token as a **`Bearer`** token in the **`Authorization`** header of their request when contacting Passport-protected routes. When utilizing the Guzzle HTTP library, for instance:

```
use Illuminate\Support\Facades\Http;
$response = Http::withHeaders([
  'Accept' => 'application/json',
  'Authorization' => 'Bearer '.$accessToken,
])->get('https://passport-app.test/api/user');
return $response->json();
```

Token Scopes

With scopes, your API customers may ask for a certain set of rights when seeking to access an account. For example, not every API customer will want the ability to place orders if you are developing an e-commerce service. Alternatively, you might let customers to see order shipment statuses by only requesting authorization. Put differently, scopes let users of your application restrict what a third-party program may do on their behalf.

Defining a scope

Using the **`Passport::tokensCan`** function in the boot method of your application's **`App\Providers\AuthServiceProvider`** class, you may specify the scopes of your API. An array containing scope names and scope descriptions can be used with the **`tokensCan`** method. Users will see the scope description on the permission approval screen, which may be anything you like to write:

```
public function boot(): void
{
  Passport::tokensCan([
    'place-alarm' => 'Place alarm',
    'check-weather' => 'Check weather',
```