```
database: vapor-app
cache: vapor-cache
build:
  - 'composer install --no-dev'
  - 'php artisan event:cache'
deploy:
  - 'php artisan migrate --force'
```

When a deployment hook fails, you may see the output / logs via the deployment detail tab in the Vapor UI.

Also, if you use the **`vapor deploy`** command to deploy your application, the CLI output will include the unsuccessful hook output. Of course, you may inspect the output at any moment by utilizing the **`hook:output`** for output:

```
vapor hook:output {DEPLOYMENT_HOOK_ID}
```

Using the **`hook:log`** command, you may examine the logs connected with the unsuccessful:

```
vapor hook:log {DEPLOYMENT_HOOK_ID}
```

Development

To return binary replies from your Vapor application, such as PDF downloads, your HTTP response should contain the **`X-Vapor-Base64-Encode`** header:

```
return $response->withHeaders([
  'X-Vapor-Base64-Encode' => 'True',
]);
```

Configure OpenSSL

OpenSSL stands out as a widely employed open-source software library, furnishing an array of cryptographic functions and protocols. In the realm of Laravel applications or any web-based application, OpenSSL assumes a pivotal role in safeguarding the security of both data transmission and storage.

Here are some fundamental aspects of OpenSSL in the context of a Laravel application: