bool(true)
string(1) "b"
bool(true)
Output of the above example in PHP 5.4:
string(1) "b"
bool(true)

Warning: Illegal string offset '1.0' in /tmp/t.php on line 7
string(1) "b"
bool(false)

Warning: Illegal string offset 'x' in /tmp/t.php on line 9
string(1) "a"
bool(false)
string(1) "b"
(bool(false

4.2.4 Converting to String

A value can be converted to a string using the *(string)* cast or the strval() function. String conversion is automatically done in the scope of an expression where a string is needed. This happens when using the echo or print functions, or when a variable is compared to a string.

A boolean TRUE value is converted to the string *"1"*. Boolean FALSE is converted to "" (the empty string). This allows conversion back and forth between boolean and string values.

An integer or float is converted to a string representing the number textually (including the exponent part for floats). Floating point numbers can be converted using exponential notation (*4.1E+6*).

The decimal point character is defined in the script's locale (category LC_NUMERIC).

Arrays are always converted to the string *"Array"*; because of this, echo and print can not by themselves show the contents of an array. To view a single element, use a construction such as *echo $arr['foo']*.

In order to convert objects to string magic method __toString must be used.

Resources are always converted to strings with the structure *"Resource id #1"*, where *1* is the resource number assigned to the resource by PHP at runtime. While