```
echo "Salary of qadir is ".  $salaries['qadir']. "<br
/>";
echo "Salary of zara is ".  $salaries['zara']. "<br />";
?>

</body>
</html>
```

This will produce the following result –

```
Salary of mohammad is 2000
Salary of qadir is 1000
Salary of zara is 500
Salary of mohammad is high
Salary of qadir is medium
Salary of zara is low
```

5.2.3 Identifying Elements of an Array

Before we look at creating an array, let us look at the structure of an existing array. You can access specific values from an existing array using the array variable's name, followed by the element's key, or index, within square brackets:

```
$age['fred']
$shows[2]
```

The key can be either a string or an integer. String values that are equivalent to integer numbers (without leading zeros) are treated as integers. Thus, $array[3] and $array['3'] reference the same element, but $array['03'] references a different element. Negative numbers are valid keys, but they do not specify positions from the end of the array as they do in Perl.

You do not have to quote single-word strings. *For instance*, $age['fred'] is the same as $age[fred]. However, it is considered good PHP style to always use quotes, because quoteless keys are indistinguishable from constants. When you use a constant as an unquoted index, PHP uses the value of the **constant** as the index and emits a warning:

```
define('index', 5);
echo $array[index];              // retrieves $array[5], not $array['index'];
```

Keyword

Constant is a value that cannot be altered by the program during normal execution, i.e., the value is constant.