The values in an array can themselves be arrays. This lets :you easily create multidimensional arrays

```
$row0 = array(1, 2, 3);
$row1 = array(4, 5, 6);
$row2 = array(7, 8, 9);
$multi = array($row0, $row1, $row2);
```

You can refer to elements of multidimensional arrays by appending more []s:

```
$value = $multi[2][0];                // row 2, column 0. $value = 7
```

To interpolate a lookup of a multidimensional array, you must enclose the entire array lookup in curly braces:

```
echo("The value at row 2, column 0 is {$multi[2][0]}\n");
```

:Failing to use the curly braces results in output like this

```
The value at row 2, column 0 is Array[0]
```

Example

In this example we create a two dimensional array to store – marks of three students in three subjects

This example is an associative array, you can create numeric array in the same fashion.

```
<html>
   <body>

      <?php
         $marks = array(
            "mohammad" => array (
               "physics" => 35,
               "maths" => 30,
               "chemistry" => 39
            ),

            "qadir" => array (
               "physics" => 30,
               "maths" => 32,
               "chemistry" => 29
```

Did You Know?

Heinz Rutishauser's programming language Superplan (1949–1951) included multi-dimensional arrays. Rutishauser however although describing how a compiler for his language should be built, did not implement one. Assembly languages and low-level languages like BCPL generally have no syntactic support for arrays. Because of the importance of array structures for efficient computation, the earliest high-level programming languages, including FORTRAN (1957), COBOL(1960), and Algol 60 (1960), provided support for multi-dimensional arrays.