string ifx_errormsg(integer error)

Use ifx_errormsg to fetch a description of an error given its code. This is the same numerical code returned by the ifx_error function. If no error code is supplied, the description of the last error is returned.

array ifx_fetch_row(integer result, integer position) array ifx_fetch_row(integer result, string position)

The ifx_fetch_row function returns a row from a result set after executing a select. The returned array will contain elements named in the query indexed by column names. If cursor type was set using IFX_SCROLL, then you may use the position argument. This can be an integer, or one of these strings: FIRST, NEXT, LAST, PREVIOUS, CURRENT.

array ifx_fieldproperties(integer result)

The ifx_fieldproperties function returns an array containing information about each column in a result set. The elements of the array are indexed by the column names. Each element contains a list of properties separated by semicolons. The parts of this string are type, length, precision, scale, and a flag for whether the column can be null. The type is one of the strings listed in ifx_fieldtypes.

array ifx_fieldtypes(integer result)

The ifx_fieldtypes function returns an array describing the type for eachcolumn in the result set. Possible values are SQLBOOL, SQLBYTES, SQLCHAR, SQLDATE, SQLDECIMAL, SQLDTIME, SQLFLOAT, SQLINT, SQLINT8, SQLINTERVAL, SQLLVARCHAR, SQLMONEY, SQLNCHAR, SQLNVCHAR, SQLSERIAL, SQLSERIAL8, SQLSMFLOAT, SQLSMINT, SQLTEXT, SQLUDTFIXED, SQLVCHAR. The returned array is indexed by the names of the columns.

boolean ifx_free_blob(integer blob)

The ifx_free_blob function deletes the specified blob from the database.

boolean ifx_free_char(integer character)

The ifx_free_char function deletes a character object from the database.

boolean ifx_free_result(integer result)

The ifx_free_result function frees memory associated with a result set.