```
  //free result identifier
  ifx_free_result($dbLink);

  //close connection
  ifx_close($dbLink);
?>
```

integer ifx_query(string query, integer link, integer cursor_type, array blob_id)

The ifx_query function executes a query and returns a result identifier, which most of the other Informix functions require. The link argument is as returned by ifx_pconnect, but if you leave it out, the last link established will be used. If the query is a select, you may use the IFX_SCROLL and IFX_HOLD constants for the cursor type.

If performing an update or insert, you may use a ? in the query and match it to an entry in the blob_id argument. Each entry must be a value returned by ifx_create_blob. Selects that return blob columns will return blob identifiers by default, but you can override this functionality with ifx_textasvarchar.

Note that both cursor_type and blob_id are optional. The ifx_query function will allow you to specify an array of blob identifiers for the third argument.

boolean ifx_textasvarchar(integer mode)

Use ifx_textasvarchar to control how text blobs are returned in queries. If mode is 0,

blob IDs are returned. If mode is 1, blob contents are returned.

boolean ifx_update_blob(integer blob, string data)

The ifx_update_blob function changes the contents of a blob.

boolean ifx_update_char(integer character, string data)

The ifx_update_char function changes the contents of a character object.

ifxus_close_slob

You can use ifxus_close_slob as an alias for ifxus_free_slob.

integer ifxus_create_slob(integer mode)

Use ifxus_create_slob to create a slob object. The object identifier is returned. The modes listed in Table 4 may be combined with | operators.