### *boolean msql_create_db(string database, integer link)*

The msql_create_db function attempts to create a database. The link argument is optional. If left out, the last-opened link will be used.

```
<?
  $Link = msql_connect("msql.clearink.com");
  msql_create_db("store", $Link);
  msql_close($Link);
?>
```

### *boolean msql_data_seek(integer result, integer row)*

Use msql_data_seek to move the internal row pointer to the specified row in a result set. The result argument is as returned by msql_query.

```
  $Link = msql_connect("msql.clearink.com");
  msql_select_db("store", $Link);

  $Result = msql_query("SELECT Name FROM customer", $Link);

  // jump to tenth customer
  msql_data_seek($Result, 10);

  $Row = msql_fetch_row($Result);

  print($Row[0]);

  msql_close($Link);
?>
```

### *integer msql_db_query(string database, string query, integer link)*

The msql_db_query function is identical to msql_query except that it specifies a database rather than using the database selected with msql_ select_db. The query is executed in the specified database and a result identifier is returned.

```
<?
  $Link = msql_connect("msql.clearink.com");
  $Query = "DELETE FROM customer";
  $Result = msql_db_query("store", $Query, $Link);

  $RowsAffected = msql_affected_rows($Link);
  print($RowsAffected . " rows deleted.");

  msql_close($Link);
?>
```

### *boolean msql_drop_db(string database, integer link)*

The msql_drop_db function removes an entire database from the server. The link argument is optional and, if omitted, the last connection opened will be used.