```
<?
  //connect to server as freetrade user, no password
  $dbLink = mysql_pconnect("localhost", "freetrade", "");

  //select the 'freetrade' database
  mysql_select_db("freetrade", $dbLink);

  //try to execute a bad query (missing fields)


  $Query = "SELECT FROM tax ";
  if(!($dbResult = mysql_query($Query, $dbLink)))
  {
    // get error and error number
    $errno = mysql_errno($dbLink);
    $error = mysql_error($dbLink);

    print("ERROR $errno: $error<BR>\n");
  }
?>
```

### *string mysql_error(integer link)*

Use mysql_error to get the textual description of the error for the last database action. If the optional link identifier is left out, the last connection will be assumed.

### *array mysql_fetch_array(integer result, integer type)*

The mysql_fetch_array function returns an array that represents all the fields for a row in the result set. Each call produces the next row until no rows are left, in which case FALSE is returned. By default, each field value is stored twice: once indexed by offset starting at zero and once indexed by the name of the field. This behavior can be controlled with the type argument. If the MYSQL_NUM constant is used, elements will be indexed by field numbers only. If the MYSQL_ASSOC constant is used, elements will be index by field names only. You can also use MYSQL_BOTH to force the default.

Compare this function to mysql_fetch_object and mysql_fetch_row.

### *object mysql_fetch_field(integer result, integer field)*

Use the mysql_fetch_field function to get information about a field in a result set. Fields are numbered starting with zero. The return value is an object with properties described in Table 7.

If the field argument is left out, the next field in the set will be returned. This behavior allows you to loop through each field easily.