```
<?
  //connect to server as freetrade user, no password
  $dbLink = mysql_pconnect("localhost", "freetrade", "");

  //select the 'freetrade' database
  mysql_select_db("freetrade", $dbLink);

  //get everything from address table
  $Query = "SELECT * " .
    "FROM address ";
  $dbResult = mysql_query($Query, $dbLink);

  //get field lengths
  $lengths = mysql_fetch_lengths($dbResult);

   //print length of the third column
   print($lengths[2]);
?>
```

object mysql_fetch_object(integer result)

The mysql_fetch_object function is similar to mysql_fetch_array and mysql_fetch_row. Instead of an array, it returns an object. Each field in the result set is a property in the returned object. Each call to mysql_fetch_object returns the next row, or FALSE if there are no rows remaining. This allows you to call mysql_fetch_object in the test condition of a while loop to get every row.

```
<?
  //connect to server as freetrade user, no password
  $dbLink = mysql_pconnect("localhost", "freetrade", "");

  //select the 'freetrade' database
  mysql_select_db("freetrade", $dbLink);

  //get unique cities from address table
  $Query = "SELECT DISTINCT City, StateProv " .
    "FROM address ";
  $dbResult = mysql_query($Query, $dbLink);

  // get each row
  while($row = mysql_fetch_object($dbResult))
  {
    // print name
    print("$row->City, $row->StateProv<<BR>\n");
  }
?>
```

array mysql_fetch_row(integer result)

The mysql_fetch_row function returns an array that represents all the fields for a row in the result set. Each call produces the next row until no rows are left, in which case FALSE is returned. Each field value is indexed numerically, starting with zero.