```
<?
  //connect to server as freetrade user, no password
  $dbLink = mysql_pconnect("localhost", "freetrade", "");

  //select the 'freetrade' database
  mysql_select_db("freetrade", $dbLink);

  //get everything from address table
  $Query = "SELECT * " .
    "FROM address ";
  $dbResult = mysql_query($Query, $dbLink);


  //skip to second field
  mysql_field_seek($dbResult, 1);

  //get description of each field
  while($Field = mysql_fetch_field($dbResult))
  {
    print($Field->table, $Field->name, $Field->type<BR>\N");
  }
?>
```

string mysql_field_table(integer result, integer field)

The mysql_field_table function returns the name of the table for the specified field. If an alias is used, as in the example, the alias is returned.

```
<?
  //connect to server as freetrade user, no password
  $dbLink = mysql_pconnect("localhost", "freetrade", "");

  //select the 'freetrade' database
  mysql_select_db("freetrade", $dbLink);

  //get everything from user table
  //get everything from address table
  $Query = "SELECT * " .
    "FROM address a, user u " .
    "WHERE u.Address = a.ID ";

  $dbResult = mysql_query($Query, $dbLink);

  $Fields = mysql_num_fields($dbResult);
  for($i = 0; $i  $Fields; $i++)
  {
    print(mysql_field_table($dbResult, $i) . "<BR>\n");
  }
?>
```