### *string mysql_field_type(integer result, integer field)*

Use mysql_field_type to get the type of a particular field in the result set.

### *boolean mysql_free_result(integer result)*

Use mysql_free_result to free any memory associated with the specified result set. This is not strictly necessary, as this memory is automatically freed when a script finishes executing.

```
<?
  // connect to server
  $Link = mysql_connect("localhost", "httpd", "");

  // select the 'store' database
  mysql_select_db("store", $Link);

  // get everything from customer table
  $Query = "SELECT * FROM customer ";
  $Result = mysql_query($Query, $Link);

  // free result set
  mysql_free_result($Result);
?>
```

### *integer mysql_insert_id(integer link)*

After inserting into a table with an auto_increment field, the mysql_insert_id function returns the id assigned to the inserted row. If the link argument is left out, the most recent connection will be used.

```
<?
  //connect to server as freetrade user, no password
  $dbLink = mysql_pconnect("localhost", "freetrade", "");

  //select the 'freetrade' database
  mysql_select_db("freetrade", $dbLink);

  //insert a row
  $Query = "INSERT INTO user (Login, Password) " .
    "VALUES('leon', 'secret') ";
  $dbResult = mysql_query($Query, $dbLink);

  //get id
  print("ID is " . mysql_insert_id($dbLink));
```

### *integer mysql_list_dbs(integer link)*

The mysql_list_dbs function queries the server for a list of databases. It returns a result pointer that may be used with mysql_fetch_row and similar functions.