integer mysql_num_rows(integer result)

The msyql_num_rows function returns the number of rows in a result set.

integer mysql_pconnect(string host, string user, string password)

The mysql_pconnect function operates like mysql_connect except that the connection will be persistent. That is, it will not be closed when the script ends. The connection will last as long as the server process lasts, so that if a connection is attempted later from the same process, the overhead of opening a new connection will be avoided.

```
<?
  //open persistent connection
  $dbLink = mysql_pconnect("localhost", "freetrade", "");
?>
```

integer mysql_query(string query, integer link)

Use mysql_query to execute a query. If the link argument is omitted, the last connection made is used. If there has been no previous connection, PHP will connect to the local host. If the query performs an insert, delete, or update, a boolean value will be returned. Select queries return a result identifier.

string mysql_result(integer result, integer row, string field)

The mysql_result function returns the value of the specified field in the specified row. The field argument may be a number, in which case it is considered a field offset. It may also be the name of a column, either with the table name or without. It could also be an alias.

In general, this function is very slow. It's better to use mysql_fetch_row or a similar function.

```
<?
      //connect to server as freetrade user, no password
      $dbLink = mysql_connect("localhost", "freetrade", "");

      //select the 'freetrade' database
      mysql_select_db("freetrade", $dbLink);

      // get everything from customer table
      $Query = "SELECT * FROM " .
            "user u " .
            "WHERE u.Login like 'A%' ";
      $dbResult = mysql_query($Query, $dbLink);
```