Most of the database with native support in PHP can also be accessed via ODBC. There are also numerous databases that can only be accessed viaODBC by PHP. Two that others have tried are Solid and Empress.

Stig Bakken, Andreas Karajannis and Frank Kromann have contributed to the creation of the ODBC extension.

boolean odbc_autocommit(integer connection, boolean on)

The odbc_autocommit function sets whether queries are automatically committed when executed. By default this is on. The connection argument is an integer returned by the odbc_connect or odbc_pconnect functions. This function has to be used intelligently, as not all ODBC drivers support commits and rollbacks.

```
<?
      $Connection = odbc_connect("store", "sa", "sa");

      // turn off autocommit
      odbc_autocommit($Connection, FALSE);
?>
```

boolean odbc_binmode(integer result, integer mode)

Use odbc_binmode to set the way binary columns return data for a result set. When binary data are returned by the driver, each byte is represented by hexadecimal codes. By default, PHP will convert these codes into raw binary data. If you have to use the odbc_longreadlen function to set the maximum length of long data to anything other than zero, then the modes in Table 8 apply. If the maximum read length is zero, the data are always converted to raw binary data.

```
<?
       // get a GIF from a database and send it to browser

       // connect to database
       $Connection = odbc_connect("store", "admin", "secret");

       // execute query
       $Query = "SELECT picture ";

$Query .= "FROM employee ";
$Query .= "WHERE id=17 ";
$Result = odbc_do($Connection, $Query);

// make sure binmode is set for binary pass through
odbc_binmode($Result, ODBC_BINMODE_PASSTHRU);

// make sure longreadlen mode
// is set for echo to browser
odbc_longreadlen($Result, 0);
```