```
<?
        // connect to database three times
        $Connection1 = odbc_connect("store", "guest", "guest");
        $Connection2 = odbc_connect("store", "guest", "guest");
        $Connection3 = odbc_connect("store", "guest", "guest");

        // close all the connections
        odbc_close_all();
?>
?>
```

### *boolean odbc_commit(integer connection)*

Use odbc_commit to commit all pending actions for the specified connection. If automatic commit is turned on, as is default, this function has no effect. Also, make sure your driver supports transactions before using this function.

```
<?
         // connect to database
         $Connection = odbc_connect("store", "guest", "guest");

         // turn off autocommit
         odbc_autocommit($Connection, FALSE);

         // put everything on sale
         $Query = "UPDATE catalog ";
         $Query .= "SET price = price * 0.9 ";
         $Result = odbc_do($Connection, $Query);

        // commit
        if(odbc_commit($Connection))
        {
              print("Commit successful!<BR>\n");
        }

        odbc_close($Connection);
?>
```

### *integer odbc_connect(string dsn, string user, string password, integer cursor_type)*

Use odbc_connect to connect to an ODBC data source. The user and password arguments are required, so if your driver does not require them, pass empty strings. The optional cursor_type argument forces the use of a particular cursor so that you may avoid problems with some ODBC drivers. Using the SQL_CUR_USE_ODBC constant for cursor type may avoid problems with calling stored procedures or getting row numbers.